## 20K CAST STAINLESS STEEL Y TYPE STRAINER SCREWED ENDS

KITZ Fig: UYM

Sizes: 1/4-3inch(8-80mm) 40 メッシュ スクリーン

Standards

End to End: KITZ STANDARD
End Connection: JIS B0203
Wall Thickness: KITZ STANDARD

Test Standard . KITZ STANDARD Conform to

RoHS, JV 8-80 mm (1/4-3 inch)

approved

## Dimensions

SIZE(inch/m	ım)	L	L1	н	D1	Kg
1/4	8	65.0	0.0	50.0	0.0	0.00
3/8	10	70.0	0.0	50.0	0.0	0.00
1/2	15	85.0	0.0	58.0	0.0	0.00
3/4	20	100.0	0.0	64.0	0.0	0.00
1	25	115.0	0.0	76.0	0.0	0.00
11/4	32	135.0	0.0	89.0	0.0	0.00
11/2	40	150.0	0.0	98.0	0.0	0.00
2	50	180.0	0.0	115.0	0.0	0.00
21/2	65	220.0	0.0	156.0	0.0	0.00
3	80	250.0	0.0	192.0	0.0	0.00



NAME OF PART	MATERIAL	SPECIFICATION
BODY	STAINLESS STEEL	A351 Gr. CF8M/SCS14A
COVER	STAINLESS STEEL	A351 Gr. CF8M/SCS14A

**Specifications** 

20K CAST STAINLESS STEEL Y TYPE STRAINER SCREWED ENDS, 40 メッシュスクリーン

スクリーン


End to End : KITZ STANDARD, End Connection : JIS B0203, Wall Tchickness : KITZ STANDARD, Test Standard : KITZ STANDARD, Sizes :

1/4-3inch(8-80mm), Conform to : RoHS, JV 8-80 mm (1/4-3

inch), BODYMATERIAL :STAINLESS STEEL, COVERMATERIAL :STAINLESS

STEEL, KITZ Fig : UYM





Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



