TYPE 600 FORGED BRASS, BALL VALVES

KITZ Fig: SZA

Sizes: 1/4-4inch(8-100mm)

Standards

. End to End: KITZ STANDARD . End Connection: JIS B0203 . Wall Thickness: KITZ STANDARD

Test Standard
. KITZ STANDARD

Dimensions

SIZE(inch/mm)		L	L1	Н	D1	Kg
1/4	8	42.0	0.0	37.0	70.0	0.00
3/8	10	42.0	0.0	37.0	70.0	0.00
1/2	15	53.0	0.0	40.0	80.0	0.00
3/4	20	60.0	0.0	44.0	80.0	0.00
1	25	72.0	0.0	50.0	110.0	0.00
11/4	32	84.0	0.0	55.0	110.0	0.00
11/2	40	92.0	0.0	65.0	150.0	0.00
2	50	110.0	0.0	72.0	150.0	0.00
21/2	65	138.0	0.0	101.0	200.0	0.00
3	80	167.0	0.0	113.0	300.0	0.00
4	100	193.0	0.0	131.0	300.0	0.00

Material List

NAME OF PART	MATERIAL	SPECIFICATION	
BODY	BODY FORGED BRASS		
BODY CAP	FORGED BRASS	C3771	
STEM	BRASS	C3604(4)	
BALL	FORGED BRASS	C3771(2)	




TYPE 600 FORGED BRASS, BALL VALVES

End to End: KITZ STANDARD, End Connection: JIS B0203, Wall Tchickness: KITZ STANDARD, Test Standard: KITZ STANDARD, Sizes: 1/4-4inch(8-100mm), B0DYMATERIAL: FORGED BRASS, B0DY CAPMATERIAL: FORGED BRASS, STEMMATERIAL: BRASS, BALLMATERIAL: FORGED BRASS, KITZ

Fig: SZA





For more details, please refer to the drawing.

Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



