10K DUCTILE IRON GLOBE VALVE SCREWED ENDS

KITZ Fig: 10SJ

Sizes: 1/4-3inch(8-80mm)
SCREWED BONNET, INSIDE SCREW.

Standards

• End to End: KITZ STANDARD
• End Connection: JIS B0203
• Wall Thickness: KITZ STANDARD

Test Standard . KITZ STANDARD Conform to

MLIT 8-50 mm (1/4-2 inch)

approved

Dimensions

SIZE(inch/	/mm)	L	L1	н	D1	Kg
1/4	8	50.0	0.0	108.0	60.0	0.00
3/8	10	55.0	0.0	108.0	60.0	0.00
1/2	15	65.0	0.0	122.0	70.0	0.00
3/4	20	80.0	0.0	124.0	80.0	0.00
1	25	90.0	0.0	146.0	90.0	0.00
11/4	32	105.0	0.0	161.0	100.0	0.00
11/2	40	120.0	0.0	181.0	115.0	0.00
2	50	140.0	0.0	198.0	135.0	0.00
21/2	65	180.0	0.0	256.0	180.0	0.00
3	80	200.0	0.0	276.0	225.0	0.00



NAME OF PART	MATERIAL	SPECIFICATION	
BODY	DUCTILE IRON	FCD-S	
BONNET	DUCTILE IRON	FCD-S	
STEM	STAINLESS STEEL	SUS420J2	
DISC	STAINLESS STEEL	403SS	



10K DUCTILE IRON GLOBE VALVE SCREWED ENDS, SCREWED BONNET, INSIDE SCREW


End to End : KITZ STANDARD, End Connection : JIS B0203, Wall Tchickness : KITZ STANDARD, Test Standard : KITZ STANDARD, Sizes :

1/4-3inch(8-80mm), Conform to : MLIT 8-50 mm (1/4-2

inch), BODYMATERIAL :DUCTILE IRON, BONNETMATERIAL :DUCTILE IRON, STEMMATERIAL :STAINLESS STEEL, DISCMATERIAL :STAINLESS

STEEL, KITZ Fig: 10SJ





Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



