10K DUCTILE IRON GLOBE VALVE FLANGED ENDS

KITZ Fig: 10SJBF Sizes: 3/8-3inch(10-80mm)

SCREWED BONNET, INSIDE SCREW, FLAT FACE FLANGED ENDS.

Standards

• End to End: KITZ STANDARD
• End Connection: JIS B2239 10K
• Wall Thickness: KITZ STANDARD

Test Standard . KITZ STANDARD Conform to

MLIT 10-50 mm (3/8-2 inch)

approved

Dimensions

SIZE(inch/m	nm)	L	LI	н	D1	Kg
3/8	10	85.0	0.0	108.0	60.0	0.00
1/2	15	85.0	0.0	122.0	70.0	0.00
3/4	20	95.0	0.0	124.0	80.0	0.00
1	25	110.0	0.0	146.0	90.0	0.00
11/4	32	130.0	0.0	161.0	100.0	0.00
11/2	40	150.0	0.0	181.0	115.0	0.00
2	50	180.0	0.0	198.0	135.0	0.00
21/2	65	210.0	0.0	256.0	180.0	0.00
3	80	240.0	0.0	276.0	225.0	0.00

Material List

NAME OF PART	MATERIAL	SPECIFICATION		
BODY	DUCTILE IRON	FCD-S		
BONNET	DUCTILE IRON	FCD-S		
STEM	STAINLESS STEEL	SUS420J2		
DISC	STAINLESS STEEL	403SS		

Specifications


10K DUCTILE IRON GLOBE VALVE FLANGED ENDS, SCREWED BONNET, INSIDE SCREW, FLAT FACE FLANGED ENDS.

End to End : KITZ STANDARD, End Connection : JIS B2239 10K, Wall Tchickness : KITZ STANDARD, Test Standard : KITZ STANDARD, Sizes :

3/8-3inch(10-80mm), Conform to: MLIT 10-50 mm (3/8-2 inch), BODYMATERIAL: DUCTILE IRON, BONNETMATERIAL: DUCTILE IRON, STEMMATERIAL: STAINLESS

STEEL, KITZ Fig: 10SJBF





Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



