10K DUCTILE IRON GLOBE VALVE FLANGED ENDS

KITZ Fig: 10SPB0F Sizes: 2-8inch(50-200mm)

BOLTED BONNET, OUTSIDE SCREW & YOKE, FLAT FACE FLANGED ENDS.

Standards

. End to End: JIS B2002

End Connection: JIS B2239 10K
Wall Thickness: KITZ STANDARD

Test Standard . KITZ STANDARD Conform to

MLIT 50-200 mm (2-8 inch)

approved

Dimensions

SIZE(in	ch/mm)	L	L1	н	D1	Kg
2	50	203.0	0.0	308.0	200.0	0.00
21/2	65	216.0	0.0	311.0	225.0	0.00
3	80	241.0	0.0	352.0	250.0	0.00
4	100	292.0	0.0	371.0	250.0	0.00
5	125	356.0	0.0	459.0	300.0	0.00
6	150	406.0	0.0	526.0	350.0	0.00
8	200	495.0	0.0	589.0	400.0	0.00

Material List

NAME OF PART	MATERIAL	SPECIFICATION	
BODY	DUCTILE IRON	FCD-S	
BONNET	DUCTILE IRON	FCD-S	
STEM	STAINLESS STEEL	403SS	
DISC	STAINLESS STEEL	FCD-S	

Specifications


10K DUCTILE IRON GLOBE VALVE FLANGED ENDS, BOLTED BONNET, OUTSIDE SCREW & YOKE, FLAT FACE FLANGED ENDS.

End to End : JIS B2002, End Connection : JIS B2239 10K, Wall Tchickness : KITZ STANDARD, Test Standard : KITZ STANDARD, Sizes :

2-8inch(50-200mm), Conform to: MLIT 50-200 mm (2-8 inch), BODYMATERIAL: DUCTILE IRON, BONNETMATERIAL: DUCTILE IRON, STEMMATERIAL: STAINLESS STEEL, DISCMATERIAL: STAINLESS

STEEL, KITZ Fig: 10SPB0F





Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



