## 10K CAST BRONZE BALL VALVE SCREWED ENDS WITH PNEUMATIC ACTUATOR

KITZ Fig: C-TNE Sizes: 1/4-2inch(8-50mm)

3-WAY 2 SEAT L-PORT, REDUCED BORE, DOUBLE ACTING TYPE.

Standards

End to End: KITZ STANDARD
 End Connection: JIS B0203
 Wall Thickness: KITZ STANDARD

Test Standard
. KITZ STANDARD

Dimensions

11110110110110						
SIZE(inch/mm)		L	L1	н	D1	Kg
1/4	8	46.0	23.0	85.0	0.0	0.00
3/8	10	46.0	23.0	85.0	0.0	0.00
1/2	15	67.0	33.5	93.0	0.0	0.00
3/4	20	68.0	34.0	98.0	0.0	0.00
1	25	79.0	39.5	102.0	0.0	0.00
11/4	32	89.0	44.5	125.0	0.0	0.00
11/2	40	100.0	50.0	138.0	0.0	0.00
2	50	115.0	57.5	144.0	0.0	0.00
		1	I	1		

## Material List NAME OF PART MATERIAL SPECIFICATION BODY CAST BRONZE CAC406 BODY CAP FORGED BRASS C3771 STEM HIGH TENSION BRASS C6782 BALL DEZINCIFICATION RESISTANT BRASS C3531




10K CAST BRONZE BALL VALVE SCREWED ENDS WITH PNEUMATIC ACTUATOR, 3-

WAY 2 SEAT L-PORT, REDUCED BORE, DOUBLE ACTING TYPE.

End to End: KITZ STANDARD, End Connection: JIS B0203, Wall Tchickness: KITZ STANDARD, Test Standard: KITZ STANDARD, Sizes: 1/4-2inch(8-50mm), B0DYMATERIAL: CAST BRONZE, B0DY CAPMATERIAL: FORGED BRASS, STEMMATERIAL: HIGH TENSION BRASS, BALLMATERIAL

:DEZINCIFICATION RESISTANT BRASS, KITZ Fig : C-TNE





- For more details, please refer to the drawing

Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



