10K CAST STAINLESS STEEL BALL VALVE SCREWED ENDS WITH PNEUMATIC ACTUATOR

KITZ Fig: C-UTE Sizes: 1/4-2inch(8-50mm)

REDUCED BORE, DOUBLE ACTING TYPE

Standards

End to End: KITZ STANDARD
End Connection: JIS B0203
Wall Thickness: KITZ STANDARD

Test Standard . KITZ STANDARD Conform to

RoHS 8-50 mm (1/4-2 inch)

approved

Dimensions

SIZE(inch,	/mm)	L	L1	Н	D1	Kg
1/4	8	44.0	21.0	85.0	0.0	0.00
3/8	10	44.0	21.0	85.0	0.0	0.00
1/2	15	56.5	27.5	86.0	0.0	0.00
3/4	20	59.0	30.0	88.0	0.0	0.00
1	25	71.0	36.0	91.0	0.0	0.00
11/4	32	78.0	40.0	128.0	0.0	0.00
11/2	40	83.0	42.5	131.0	0.0	0.00
2	50	100.0	51.0	137.0	0.0	0.00

Material List

NAME OF PART	MATERIAL	SPECIFICATION	
BODY	STAINLESS STEEL	A351 Gr. CF8M/SCS14A	
STEM	STAINLESS STEEL	316\$\$	
BALL	STAINLESS STEEL	316SS	

Specifications

10K CAST STAINLESS STEEL BALL VALVE SCREWED ENDS WITH PNEUMATIC ACTUATOR, REDUCED BORE, DOUBLE ACTING TYPE


End to End: KITZ STANDARD, End Connection: JIS B0203, Wall Tchickness: KITZ STANDARD, Test Standard: KITZ STANDARD, Sizes:

1/4-2inch(8-50mm), Conform to : RoHS 8-50 mm (1/4-2

inch), BODYMATERIAL :STAINLESS STEEL, STEMMATERIAL :STAINLESS

STEEL, BALLMATERIAL :STAINLESS STEEL, KITZ Fig : C-UTE





For more details, please refer to the drawing.

Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



